



FUTER BED, CONSTRUCTED WETLAND & DEWATS FOR DISCHARGE POINT DRAINTREATMENT IN NAMAM GANGE DISTRICT, HOOGHLY

Presented by-

PANCHAYATS AND RURAL DEVELOPMENT DEPARTMENT, WEST BENGAL

Overview of Hooghly District

- Hooghly river forms the eastern border of the district.
- 12 (twelve) GPs of Chinsurah and Balagarh blocks are *Namami Gange* GP.
- Untreated liquid waste is a source of pollution for the river Ganges.
- GWM initiatives have been made to arrest flow of untreated grey water into Ganges.



Sr No	Particulars	Details		
1	Total No of Blocks	18		
2	Total No of GP	207		
3	Total no of Villages	2,115		
4	Total Population (2023)	44,79,591		
5	Total Household (2023)	9,95,465		

DETAILS OF GANGA BORDERING GP

No. of Blocks: 2

No. of Gram Panchayats: 12

No. of villages: 115

Total population: 2,30,623

Total household: 39.186

No. of drains: 307

No. of drains outlet to Ganga river: 39

No. of leach pit: 167


No. of filter chamber: 188

No. of constructed wetland: 3


No. of DEWATS: 2

IMPLEMENTATION PLAN


☐ <u>Steps for LWM Implementation</u>




Five Days of Handholding Support to district technical persons by State GWM experts




Field level demonstration




State Team Support for Design and Estimation of LWM Assets



Monitoring GWM progress by district and state team



Planning and DPR preparation of GWM in all villages by NS with Vetting of DPR by district officials



Time-to-Time Capacity Building and Training on GWM

STEP-1: 5 Days Handholding Support for District GWM

■ Methodology Adopted for the Training

DAY 1- Detailed Orientation

 Classroom Orientation on GWM and field visit of District/ Block/ ISGP/ MGNREGS Engineers, Joint BDOs, and Nirman Sahayaks facilitated by GWM experts

DAY 2 to 4- Field Visit and Data Collection

• During the period, team lead by Nirman Sahayak identified the probable intervention sites and collected requisite data

DAY 5- Meeting and Drawing Preparation

Based on the information collected, appropriate technologies of GWM were discussed






DAY 1
ORIENTATION







DAY 2 to 4 FIELD SURVEY















DAY 5 INTERACTIVE SESSION











STEP-2&3: State Team Support for Preparation of Drawing and Estimate


☐ Assistance in preparation of Drawing & Estimates:

Sr No	Description	Amendments	
1	Technical intervention on GWM with selection criteria	F:\New folder\ hnical intervention	
2	GWM technical advisory	F:\New folder\ I technical advisory	
3	Construction of silt chamber advisory	F:\New folder\ stuction of silt chai	
4	Model Estimate for DEWATS, Constructed Wetland, Filter Chamber, Leach Pit	F:\New folder\ del estimate GWM	
5	Model Estimate of Integrated Settler with ABR	F:\New folder\ ;4-PRD_08112023. ₄	
6	Fund Utilization	F:\New folder\ WM clarification.p	

^{*}Model Estimate assisted the district team to prepare and check the estimates properly

STEP-4: Field Demonstration

□ Support from State Team



*As these were new type of construction hence it was required for proper implementation

STEP-5: Review and Monitoring by District and State Team

☐ Review Meeting for assessment of progress of district



Regular monitoring by State through review meetings






Field Inspection by State and District Teams




STEP-6: Capacity Building and Training

☐ Broad Objectives of the Support:







DEWATS

at Nayasarai Village, Chandrahati 1





After

Treated Water

- Planned for treatment of greywater from **100 households**
- Components are settler tank, anaerobic baffle filter tank, and a polishing pond filled with gravel
- Capacity 25 KLD

Influent Wastewater

- The total project cost is **5 lakhs**.
- The treated water is discharged into the Kunti River, a tributary of the Ganges..

Construction of DEWATS



Drain carries Grey water



Grey water comes into settler tank





HPGF



Water comes into ABR



Treated Water comes into Polishing Pond

PHASES OF CONSTRUCTION OF DEWATs

CONSTRUCTED WETLAND

at Nayasarai Village, Chandrahati 1





Before After

Ongoing Construction

- Planned for greywater from 80 HHs
- Components are settler tank, Horizontal Planted Gravel Filter (HPGF) bed.
- Capacity is 15 KLD
- The total project cost is **4 lakhs**.
- Treated water is discharged into the Kunti River

DEWATS

at Bishpara Raghunathpur, Chandrahati 1







Before

After

Planned to treat grey water from 100 HHs.

- To solve this problem, **Integrated Settler with ABR** of **25 kld** capacity has been constructed.
- Initially, the BOD of wastewater was 120 mg/l, which has been successfully reduced to 27 mg/l.
- Treated water is now used for irrigation purpose.

Treated Water













COMMUNITY LEACH PIT

VERTICLE FILTER CHAMBER




BEFORE



Raghunathpur Village Chandrahati 1 GP

Bishpara Village, Chandrahati 1 GP







AT VARIOUS OUTLET POINTS OF GANGA RIVER









VERTICAL FILTER CHAMBER

at various locations in District

For Hand Pump











VERTICAL FILTER CHAMBER

At various locations in the District

For Small Drain Treatment Carrying Wastewater From 25-30 HH










TREATING WASTE WATER FLOW INTO THE GANGA



CHANDRAHATI-I GRAM PANCHAYAT

		Village Name	Household	Total Population	No of Outlet Points To Kunti River	GWM Assets	
	Sl No.					Filter Chamber	Constructed Wetland/ DEWATS
	1	Nayasarai	612	2,405	3	1	2
	2	Raghunathpur	652	2,698	3	2	1
	3	Bishpara Chapatala	541	2,164	2	2	0
	4	Bishpara Panchanantala	552	2,210	2	2	0
	5	Bishpara	580	2,321	1	1	0
	6	Chapatala	570	2,481	1	1	0
Total		Total	3,507	14,279	12	9	3

Following a comprehensive survey, **Chandrahati 1 GP in Chinsurah-mogra block** was selected for demonstration of pilot projects to manage wastewater

